

NOVA DOCK SHELTERS - GS SERIES

SURVEY

SITE SURVEY INFORMATION

Door Width: _____ FT. _____ IN.

Door Height: _____ FT. _____ IN.

Dock Height: _____ FT. _____ IN.

Distance Between Doors: _____ FT. _____ IN.

Bumper Projection*: _____ IN.

(*Includes bumper projection and any building wall/foundation offset or cantilever)

Dock Approach: Level Decline Incline % Grade _____

TRUCK/TRAILER INFORMATION

Width: _____ Max. _____ Min. _____

Hydraulic Tailgate: Yes No

Height: _____ Max. _____ Min. _____

Rear Step Section: Yes No

Length: _____ Max. _____ Min. _____

Yard Jockeys: Yes No

Tailgate/Step Section Size: _____ IN.

MODEL: GS SERIES

Side Pad Backing: Wood Galvanized Steel Channel Frame

Shelter Width: _____

Shelter Height: _____

Taper: Tapered Non-Tapered

Top Projection: 20" 24" 30" 36" 42" 48" _____

Bottom Projection: 20" 24" 30" 36" 42" 48" _____

For Projections Over 48" Consult Factory

Base Material: MAX-1000™ MAX-60™ 40 oz. Vinyl 22 oz. Vinyl 40 oz. NOVALON™**
 16 oz. NOVALON™**

Color: Black (Standard) Blue* Brown* Green*

Head Curtain Drop: 30" 36" 42" 48" 54" _____

Head Member Style: Raked Flat Steel Frame

Options: None Full Length Guide Stripes Pull Rope Assembly
 Split Head Curtain/Velcro®

* Colors available in 22 oz, 40 oz. and NOVA MAX-60 fabrics.

** NOVALON™ is the equivalent replacement for Hypalon® a trade name used by DuPont that is no longer available.

